

Form Number LLCF-061	Issue Date 03/17/16	Revision Date 01/15/25	Form Number LLCF-061
	Retractable Inspection		

Job Number: _____ Model / Name: _____

Serial Number: _____ Lot Number: _____

Date of Manufacture _____

General Factors		Accepted Rejected	Comments
1.	Impact Indicator: Inspect indicator for activation (rupture of red stitching, elongated indicator, etc.).	Accepted Rejected	
2.	Screws/Fasteners: Inspect for damage and make certain all screws and fasteners are tight.	Accepted Rejected	
3.	Housing: Inspect for distortion, cracks and other damage. Inspect anchoring loop for distortion or damage.	Accepted Rejected	
4.	Lanyard/Lifeline: Inspect for cuts, burns, tears, abrasion, frays, excessive soiling and discoloration. (See impact indicator section.)	Accepted Rejected	
5.	Locking Action: Inspect for proper lock-up of brake mechanism.	Accepted Rejected	
6.	Retraction/Extension: Inspect spring tension by pulling lanyard out fully and allowing to retract fully (lifeline must be taut with no slack).	Accepted Rejected	
7.	Hooks/Carabiners: Inspect for physical damage, corrosion, proper orientation and markings.	Accepted Rejected	
8.	Labels: Inspect, making certain all labels are securely held in place and are legible.	Accepted Rejected	
Overall Disposition:		Accepted Rejected	Inspected By: Date Inspected:

Name (print): _____ Date: _____

Signature: _____